

Sterilization, Hygiene & Maintenance



Class B, simply profitable



lina

lina



The essentials of sterilization

Simple and expandable. Lina is one of the range of W&H sterilizers which offers maximum safety and an excellent price-performance ratio with its Class B cycles and a built-in USB data log.



Class B cycles exclusively

The Lina sterilizer works exclusively with Class B cycles and with short ECO B cycles for smaller loads.



Simple navigation

All sterilization options are easily accessible with the easily operated keypad.



ECO B sterilization program

The cycle time can be reduced by half for small loads.



Built-in data log

The built-in data log means that sterilization cycles can be saved to a USB stick without needing cables and external boxes.



Barcode label printer

The LisaSafe label printer can be connected to the sterilizer to print barcodes. Combined with the built-in data log your traceability system is enhanced.

Technical data

Scan the QR code with
your mobile phone
for more information
on Lina



Pictures are for illustrative purposes only. Additional equipment
and accessories shown are not included as standard.

Lina sterilization cycles

		B-Universal 134			B-Prion 134			B-Universal 121
Temperature		134 °C			134 °C			121 °C
Holding time		3.5'			18'			15'
Total cycle duration including drying		ECO-B	Full Load	Typical Load	ECO-B	Full Load	Typical Load	Full Load
	Lina 17	29'	54'	49'	44'	69'	64'	75'
	Lina 22	33'	64'	55'	48'	79'	70'	79'
Max solid: ECO/full/typical loads/ Max porous load		Lina 17: 0.5kg / 4kg / 2kg / 1.5kg • Lina 22: 0.5kg / 5kg / 2kg / 1.8kg						

Test cycles

Helix/Bowie Dick/Vacuum test

Your advantages at a glance

- > The ECO B cycle reduces the cycle time by half
- > Low-noise operation with the patented water separation system
- > User-friendly keypad for simple navigation to all sterilization options
- > Built-in dust filter to protect internal components
- > Programmable cycle start
- > Excellent value for money
- > Integrated automatic water filling valve (optional)
- > Automatic digital cycle recording on USB stick (optional)



	Lina 17	Lina 22
Type:	PR013-003-17	PR013-003-22
Chamber size:	17 l	22 l
Power supply:	200 – 240 Vac 50 / 60 Hz; 10 A	
Power consumption	2 kW	
Dimensions overall (W x H x D):	450 x 435 x 599 mm	
Weight:	39 kg	40 kg
Main/Used water tanks:	4 / 3.5 litres	
Working range:	5 to 10 cycles	
Usable space in chamber (W x H x D):	195 x 195 x 297 mm	195 x 195 x 390 mm
Connection type:	1 serial port, 1 USB + 1 serial (optional), integrated automatic water filling valve (optional)	

Lina sterilizers were designed, certified and validated
with the most stringent Directives and Standards:

93/42/EEC	Medical Device Directive	EN 61326	Electromagnetic compatibility
97/23/EEC	Pressure equipment Directive	EN 61010-1	Safety requirements
EN 13060	Small steam sterilizer	EN 61010-2-040	Specific requirements for steam sterilizer

- > The sterilizer can be validated according to EN 17665-1

W&H Sterilization Srl.
Via Bolgara, 2
24060 Brusaporto (BG), Italy
t + 39 035-66 63 000
f + 39 035-50 96 988
office.sterilization@wh.com
wh.com